

# Safety Data Sheet

Date Printed: 13-May-2016

Version: A

## 1. IDENTIFICATION

Product Identifier: 761.15  
Product Name: WILKODURE WHITE  
Other means of Identification  
SDS#: 761.15 SDS  
Customer and Customer Product Code:  
UN/ID No.: UN 1263

### Recommended use of the product and restrictions on use

**Recommended Use:** Protective Coating.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Wilko Paint, Inc.  
2727 Ohio St.  
P.O. Box 4089  
Wichita, KS 67204

### Emergency Telephone Number

**Company Phone Number:** Toll Free: **1-800-658-3799**

**Emergency Telephone (24 hr):** Chemtrec: **1-800-424-9300**

## 2. HAZARDS IDENTIFICATION

**Physical State:** Liquid

### Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Germ cell mutagenicity	Category 1B
Flammable Liquids	Category 2

### Signal Word

**Danger**



### Hazard Statements

- Flammable liquid and vapor.
  - Harmful if swallowed.
  - Causes skin irritation.
  - Causes serious eye damage.
  - May cause respiratory irritation.
  - May cause drowsiness or dizziness.
- Other: Harmful if ingested or inhaled. See Sections 8 and 16 for more information.

### Precautionary Statements - Prevention

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.

This product contains an ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected carcinogens. As with any chemicals, ashtmatic sensitization can occur from single or repeated exposure. Strict observation of exposure limits is essential (See Section 8).

**Precautionary Statements - Response**

- If exposed or concerned: Get medical advice/attention.
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**Precautionary Statements - Storage**

Store locked up and out of reach of children, in a well-ventilated place. Keep cool.

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant.

**Other Hazards**

Harmful to aquatic life with long lasting effects.

**3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS**

Chemical Name	CAS No	Weight - %
TITANIUM DIOXIDE (IARC 2B CLASIFICACION)	13463-67-7	30-35
XYLOL / XYLENE	1330-20-7	15-20
ETHYLBENZENE	100-41-4	03-04

\*\* If chemical name is "proprietary" or CAS No. is blank, and weight % is zero or listed as a range, then the specific chemical identity and/or percentage of composition is withheld as a trade secret and any exposure limits is listed in Section 8.

**4. FIRST AID MEASURES****First Aid Measures**

- **General Advice** If exposed or concerned: Get medical advice/attention.
- **Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- **Skin Contact** Take off contaminated clothing. Wash skin with soap and water. Wash contaminated clothing before reuse.
- **Inhalation** Remove to fresh air. If not breathing, give artificial respiration.
- **Ingestion** Do not induce vomiting. Call a physician.

**Most important symptoms and effects** May cause skin and eye irritation. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Loss of coordination.

**Indication of any immediate medical attention and special treatment needed** Loss of consciousness, fainting. Blurry or loss of vision.

**Notes to Physician** Treat symptomatically.

**5. FIRE FIGHTING MEASURES****FLAMMABILITY CLASSIFICATION**

FLAMMABLE LIQUID - NFPA CLASS 3 - Flammable liquid flash point below 100 °F.

**SUITABLE EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam.

**SPECIAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon oxides

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus must be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**6. ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

- Use personal protective equipment as required.
- Prevent further leakage or spillage if safe to do so.
- Remove all sources of ignition. Ventilate the area.
- Remove with inert absorbent and place into an appropriate container for disposal.



**Appropriate engineering controls** Apply technical measures to comply with the occupational exposure limits.

**Individual protection measures, such as personal protective equipment**

<b>Eye/Face Protection</b>	Wear goggles or safety glasses with unperforated side shields.
<b>Skin and Body Protection</b>	Use solvent resistant gloves and apron or suitable protective clothing, additional use of barrier cream is recommended.
<b>Respiratory Protection</b>	<p>Apply in a spray booth with ventilation that is adequate to keep the TWA TLV below the stated limits as stated in the Section 8 table, otherwise use a positive pressure air supplied respirator (TL19C NIOSH/MSHA approved). If unavailable, a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 8 may be used as long as the TWA TLV are below stated limits. Follow respirator manufacturer's directions for use. Wear the respirator for the duration of spraying and until all vapors and mists are gone.</p> <p><b>ALL PERSONELL IN THE AREA WHERE THIS PRODUCT IS BEING USED MUST BE EQUIPPED WITH THE SAME RESPIRATOR PROTECTION RECOMMENDED FOR THE PAINTERS.</b></p> <p>Wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive, when sanding or abrading dried film.</p>

**General Hygiene Considerations:** Handle in accordance with good industrial hygiene and safety practice.

**OTHER PRECAUTIONS**

If this product is to be mixed with other components before use, read and follow warning labels on all components. Intentional misuse by deliberately concentrating and inhaling the vapors can be harmful or fatal.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical State</b>	Liquid		
<b>Appearance</b>	Paint	<b>Odor</b>	Not determined
<b>Color</b>	See description	<b>Odor Threshold</b>	Not determined
<b>Property</b>	<b>Values</b>		<b>Remarks • Method</b>
<b>pH</b>	Not determined		
<b>Melting Point/Freezing Point</b>	Not determined		
<b>Boiling Point/Boiling Range</b>	110-169 °C / 230-337 °F		
<b>Flash Point</b>	28 °C / 82 °F		
<b>Evaporation Rate</b>	Slower Than Ether		
<b>Flammability (Solid, Gas)</b>	N/A - Liquid		
<b>Upper Explosive Limit (UEL)</b>	Not determined		
<b>Lower Explosive Limit (LEL)</b>	1.00 %		
<b>Flammability Limit Vapor</b>	Not determined		
<b>Vapor Pressure</b>	Not determined		
<b>Vapor Density</b>	Heavier than air		
<b>Specific Gravity</b>	1.36		
<b>Water Solubility</b>	Not determined		
<b>Solubility in other solvents</b>	Not determined		
<b>Partition Coefficient Auto-</b>	Not determined		
<b>Ignition Temperature</b>	Not determined		
<b>Decomposition</b>	Not determined		
<b>Temperature Kinematic</b>	Not determined		
<b>Viscosity Dynamic</b>	Not determined		
<b>Viscosity</b>	Not determined		
<b>VOC</b>	2.43 #/gal or 291 gr/li		EPA Method 24
<b>VOC Actual</b>	2.43 #/gal or 291 gr/li		Total VOC per gallon, as supplied
<b>Wt/Gal</b>	11.36 #/gal		

## 10. STABILITY AND REACTIVITY

**Reactivity** Not reactive under normal conditions.  
**Chemical Stability** Stable under recommended storage conditions.  
**Possibility of Hazardous Reactions** None under normal processing.  
**Conditions to Avoid** Avoid all possible sources of ignition.  
**Incompatible Materials** Strong oxidizing agents.  
**Hazardous Decomposition Products** Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

There is no specific data available for this product.

## 12. ECOLOGICAL INFORMATION

There is no specific data available for this product.

**CAUTION:** Can be toxic to living organisms. Keep out of soil and water stream.  
**ECOTOXICITY EFFECTS:** Harmful to aquatic life with long lasting effects.  
**MOBILITY:** Not available  
**BIOACCUMULATIVE POTENTIAL:** Not available  
**PERSISTANCE / DEGRADABILITY:** Not available

## 13. DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Disposal should be in accordance with applicable regional, national and local laws and regulations. Only EPA approved facility must handle incineration if this method of disposal is chosen.

**Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations (Refer to above).

## 14. TRANSPORT INFORMATION

NOTE Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

UN/ID No	UN 1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III

IATA

UN/ID No	UN 1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III

IMDG

UN/ID No	UN 1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	III

## 15. REGULATORY INFORMATION

There is no specific data available for this product.

## 16. OTHER INFORMATION

NFPA	<b>Health Hazards</b> 2*	<b>Flammability</b> 3	<b>Instability</b> 1	<b>Special Hazards</b> Not Determined
HMIS	<b>Health Hazards</b> *2	<b>Flammability</b> 3	<b>Physical Hazards</b> 1	<b>Personal Protection</b> J,X**

Chronic Hazard Star Legend  
Personal Protection

\*2=Chronic Health Hazard.

\*\*J=Goggles, impermeable gloves, apron and vapor respirator required.

X=See your supervisor for guidance.

Issue Date: 29-Jun-1996  
Revision Date: 13-May-2016  
Version: A  
Revision Note: SDS format

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet