



WILKO PAINT
2727 Ohio Street
Wichita, KS 67219
Tel 800-658-3799
Fax 316-838-4288

COATING RECOMMENDATIONS

With Attached Product Data
Coating System No. 21

For: _____

Date: _____

SURFACE DESCRIPTION

Interior or exterior above ground concrete structures, basement walls, interior and exterior transite, galvanized or primed metal, and wood structures, exposed to ambient conditions.

COATING SYSTEM

Water borne exterior acrylic latex designed for ease of application and superior performance.

SURFACE PREPARATION

High pressure water wash to remove chalk and other surface contaminants. Spot prime as needed.

PRIME COAT (OPTIONAL)

Product	907.15 WB Primer Red (or 902-13 Gray)
No. Coats	One
Application	Brush, roller or spray
Dry Film Thickness	2.0-3.0 mils
Wet Film Thickness	5.0-7.0 mils

INTERMEDIATE COAT

Product	None required
No. Coats	
Application	
Dry Film Thickness	
Wet Film Thickness	

TOP COAT

Product	931.02 WB Acrylic Latex White (or colors)
No. Coats	One or two
Application	Brush, roller or spray
Dry Film Thickness	1.5-2.0 mils
Wet Film Thickness	4.0-6.0 mils

REMARKS: 1. See Technical Data Sheets for mixing instructions
2. For wood surfaces use 491.01 Undercoater

Please visit our website for more information: www.wilkopaintinc.com