MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME:
WILKO PAINT, INC.
2727 OHIO ST.
P.O. BOX 4089
WICHITA, KANSAS 67204-0089
TELEPHONE NO.: 316-838-4288
EMERGENCY NO.: 316-838-4288

HMIS HAZARD RATINGS:
HEALTH: *2
FLAMMABILITY: 3
REACTIVITY: 1
PERSONAL PROTECTION: J,X
DATE OF PREPARATION:
09/12/2008

SECTION I - PRODUCT INDENTIFICATION

PRODUCT NUMBER: 347.49
PRODUCT NAME: Wilkopon Red Oxide Primer w/347.49B Act. Customer: Baldor Electric Company
PRODUCT CLASS: Epoxy Based Primer

SECTION II - HAZARDOUS INGREDIENTS

DESCRIPTION	CAS NO.	PERCENT By Wt.	CARC+	OSHA EXP LIMITS(ppm) Ceil	STEL	PEL	ACGIH TLV(ppm) STEL	TWA	mg/m3	SARA 313	VP,mmHg @77 F
ACETONE	67-64-1	2.91	N	3000	1000	750	1000	750			180.00
Xylol	1330-20-7	16.62	N	300	200	100	150	100	435.00	Y	9.50
N-BUTYL ALCOHOL	71-36-3	2.98	N	50						Y	5.50
TOLUOL/TOLUENE	108-88-3	5.11	N	500	150	200	150	100	375.00	Y	22.00
ISOPROPYL ALCOHOL	67-63-0	2.33	N		500	400	500	400		Y	37.00
Silica Quartz	14808-60-7	0.00							0.10	Y	

DOES NOT CONTAIN CHLOROFLUOROCARBONS (CFC's) OR OTHER OZONE DEPLETING SUBSTANCES (ODS) IF USED UNDER NORMAL CONDITIONS.
DOES NOT CONTAIN LEAD OR OTHER REGULATED METALS.
ALL PERSONNEL HANDLING THIS PRODUCT MUST BE PROTECTED FROM ABOVE INGREDIENTS BY KEEPING EXPOSURE LIMITS BELOW MAXIMUM.
IF THIS PRODUCT IS A PART OF A MULTI-COMPONENT COATING, PRECAUTIONS FOR ALL COMPONENTS MUST BE OBSERVED AFTER MIXING.

CARC+ - 'Y' indicates that this ingredient is a suspected or is a known carcinogen. Refer to SECTION V for further details.

SECTION III - PHYSICAL DATA

BOILING RANGE: 132-282 F (56-139 C) VAPOR DENSITY: Heavier than air
EVAPORATION RATE: Slower Than Ether PERCENT VOLATILE BY VOLUME: 57.73
VOC: 3.97 #/Gal or 480 gr/li, water and VOC exempt solvents excluded, based on EPA Method 24. Wt/Gal: 11.34
Actual VOC is 3.77 #/gal. This is the total regulated VOC per gallon of paint if applied without addition of regulated solvents.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA - FLAMMABLE LIQUID - NFPA CLASS IC FLASH POINT: 82 F (28 C)
DOT - FLAMMABLE LIQUID OR SOLID LEL: 1.10
EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Isolate from heat, sparks, electrical equipment and open flame. Closed containers may explode when exposed to extreme heat. Special precautions must be exercised when applied to hot surfaces as fumes and explosive vapors may be generated.
SPECIAL FIREFIGHTING PROCEDURES: Firefighters must wear respiratory equipment to avoid inhalation of vapors. Use Water fog to cool closed containers to avoid explosion due to heat build up.
UN Classification No.: PAINT - UN 1263*