



---

SECTION V - HEALTH HAZARD DATA

---

EFFECTS OF OVEREXPOSURE: EYE CONTACT: Redness, blurred vision, temporary irritation.

INHALATION: Sensitive individuals may experience dizziness, breathing difficulty or allergic reactions.

SKIN CONTACT: Temporary irritation and dermatitis caused by defatting action on skin.

INGESTION: Can cause gastrointestinal irritation, vomiting, nausea and diarrhea.

CAUTION: Water based paint generally contain solvents. Refer to Section II for specific information.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Allergic reaction in sensitive individuals.

PRIMARY ROUTES OF ENTRY: Dermal, ingestion, inhalation.

EMERGENCY AND FIRST AID PROCEDURES: CONSULT A PHYSICIAN IN ALL CASES.

EYE CONTACT: Flush with large quantities of water for 15 minutes.

INHALATION: Move to fresh air, if breathing stops, apply artificial respiration.

SKIN CONTACT: Remove contaminated clothing and wash affected skin with soap and water.

INGESTION: Induce vomiting. CONSULT A PHYSICIAN.

OTHER HEALTH WARNING: Chemicals that are known, or are suspected carcinogen, if formulated in this product, are listed under Section II. It may also inadvertently contain, though not intentionally added, trace amounts of chemicals that are not listed that may cause cancer, birth defect or reproductive harm. Expectant mothers must not work with this or other chemicals without consulting a physician.

---

SECTION VI - REACTIVITY DATA

---

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and of metals listed, if any, under section II, and other potentially dangerous vapors and fumes.

CONDITIONS TO AVOID: High heat, sources of ignition, poor ventilation, corrosive atmosphere, freezing temperatures.

INCOMPATIBILITY (materials to avoid): Alkaline materials, strong acids and oxidizing agents.

---

SECTION VII - SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIALS IS RELEASED OR SPILLED: Eliminate ignition sources, provide good ventilation, dike spill area and apply inert absorbent to spilled liquid.

WASTE DISPOSAL METHOD: Dispose in accordance with local, state and Federal regulations.

---

SECTION VIII - SAFE HANDLING AND USE INFORMATION

---

RESPIRATORY PROTECTION: Use NIOSH approved cartridge or self contained respirator or gas mask suitable to keep airborne mists and vapor concentrations below the TWA TLV.

VENTILATION: Use mechanical ventilation to keep vapor concentration below TLV.

PROTECTIVE GLOVES: Use impermeable, solvent-resistant gloves.

EYE PROTECTION: Use splash proof safety goggles or shields for eye protection.

OTHER PROTECTIVE EQUIPMENT: Use protective clothing, aprons & head caps during application.

HYGIENIC PRACTICES: Wash hands thoroughly after handling this product and before eating.

---

SECTION IX - SPECIAL PRECAUTIONS

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid exposure to extreme temperatures. Keep covered and store in cool, dry and well-ventilated building for maximum shelf life.

OTHER PRECAUTIONS: Store at above freezing temperatures. Keep covered when not in use and keep out of reach of children. Do not drill, cut, weld, or braze empty containers. The dried film of this product may become dust nuisance when removed by sanding, blasting, or grinding; observe tlv as dust when these procedures are performed.

---

SECTION X - OTHER INFORMATION

---

REGULATORY INFORMATION: Users must determine the suitability of this product in meeting any Federal, State, or Local emission restrictions. It is also the user's responsibility that the reporting requirements of any and all agencies are met.