# Safety Data Sheet

Details of the supplier of the safety data sheet         Supplier Address         Wilko Paint, Inc.         2727 Ohio St.         P.O. Box 4089         Wichita, KS 67204         Emergency Telephone Number:         Company Phone Number:         Company Phone Number:         Toll Free:       1-800-658-3799         Emergency Telephone (24 hr):       Toll Free:         The state:       Liquid         Classification       2. HAZARDS IDENTIFICATION         Return to state:       Liquid         Classification       Signal Word         Signal Word       Signal Word         Danger       Immable Liquids         Hazard Statements       - Causes serious eye damage.         • Harmful if swallowed.       • May cause respiratory irritation.         • Causes skin irritation.       • May cause of drowsiness or dizziness.	ly. Category 4 Category 1B Category 2
WILKOPON ACTIVATOR 4:1         Other means of Identification         SDS#:       330.18B SDS         Customer and Customer Product Code:         UN/ID No.:       UN 1263         Recommended use of the product and restrictions on use         Recommended Use:       Protective Coating, this product is for use with Part A onl         Details of the supplier of the safety data sheet         Supplier Address         Wilko Paint, Inc.         2727 Ohio St.         P.O. Box 4089         Wilchita, KS 67204         Emergency Telephone Number:         Company Phone Number:         Company Phone Number:         Chastification         cust toxicity - Inhalation (Dusts/Mists)         ierm cell mutagenicity         Iammable Liquids         Signal Word         Danger         Hazard Statements         • Fammable liquid and vapor.         • Harmful if swallowed.         • Harmful if swallowed.         • Harmful if swallowed.         • May cause respiratory intration.         • May cause row siness or dizziness.	Category 4 Category 1B
Other means of Identification       330.18B SDS         Outstomer and Customer Product Code:       UN 1263         Recommended use of the product and restrictions on use       Recommended Use:         Protective Coating, this product is for use with Part A onl         Details of the supplier of the safety data sheet         Supplier Address         Wilko Paint, Inc.         2727 Ohio St.         P.O. Box 4089         Wichta, KS 67204         Emergency Telephone Number:         Company Phone Number:         Company Phone Number:         Company Phone Number:         Company Phone Number:         Causes State:         Liquid         Classification         cute toxicity - Inhalation (Dusts/Mists)         Serm cell mutagenicity         Tammable Liquids         Signal Word         Paramets         Harmful if swallowed.         - Causes serious eye damage.         - May cause respiratory irritation.         - May cause drowsiness or dizziness.	Category 4 Category 1B
SDS#: 330.18B SDS Customer and Customer Product Code: UN/ID No.: UN 1263 Recommended use of the product and restrictions on use Recommended Use: Protective Coating, this product is for use with Part A onl Details of the supplier of the safety data sheet Supplier Address Wilko Paint, Inc. 2727 Ohio St. P.O. Box 4089 Wichita, KS 67204 Emergency Telephone Number: Toll Free: 1-800-658-3799 Emergency Telephone (24 hr): Chemtrec: 1-800-658-3799 Emergency Telephone (24 hr): Chemtrec: 1-800-424-9300 2. HAZARDS IDENTIFICATION Physical State: Liquid Classification cute toxicity - Inhalation (Dusts/Mists) Ferm cell mutagenicity Tammable Liquids Signal Word Danger Hazard Statements • Flammable liquid and vapor. • Harmful if swallowed. • Causes skin irritation. • May cause derowsiness or dizziness.	Category 4 Category 1B
Customer and Customer Product Code: UN/ID No.: UN 1263 Recommended Use: Protective Coating, this product is for use with Part A onl Details of the supplier of the safety data sheet Supplier Address Wilko Paint, Inc. 2727 Ohio St. P.O. Box 4089 Wichita, KS 67204 Emergency Telephone Number: Toll Free: 1-800-658-3799 Emergency Telephone (24 hr): Chemtrec: 1-800-424-9300 2. HAZARDS IDENTIFICATION Physical State: Liquid Classification kucte toxicity - Inhalation (Dusts/Mists) ierm cell mutagenicity iammable Liquids Signal Word Danger Hazard Statements • Flammable liquid and vapor. • Harmful if swallowed. • Causes skin irritation. • Causes skin irritation.	Category 4 Category 1B
UV/ID No.: UN 1263  Recommended use of the product and restrictions on use Recommended Use: Protective Coating, this product is for use with Part A onl Details of the supplier of the safety data sheet Supplier Address Wilko Paint, Inc. 2727 Ohio St. P.O. Box 4089 Wichita, KS 67204 Emergency Telephone Number: Toll Free: 1-800-658-3799 Emergency Telephone (24 hr): Chemtrec: 1-800-458-3799 Emergency Telephone (24 hr): Chemtrec: 1-800-458-3799 Emergency Telephone (24 hr): Chemtrec: 1-800-424-9300  2. HAZARDS IDENTIFICATION Physical State: Liquid Classification ucute toxicity - Inhalation (Dusts/Mists) serm cell mutagenicity itammable Liquids  Signal Word Danger Hazard Statements • Flammable liquid and vapor. • Harmful if swallowed. • Causes serious eye damage. • May cause drowsiness or dizziness.	Category 4 Category 1B
Recommended use of the product and restrictions on use Recommended Use:       Protective Coating, this product is for use with Part A onl         Details of the supplier of the safety data sheet       Supplier Address         Supplier Address       Wilko Paint, Inc.         2727 Ohio St.       P.O. Box 4089         Wichita, KS 67204       Emergency Telephone Number:         Company Phone Number:       Toll Free:       1-800-658-3799         Emergency Telephone (24 hr):       Chemtrec:       1-800-424-9300         2. HAZARDS IDENTIFICATION       Physical State:       Liquid         Classification       scute toxicity - Inhalation (Dusts/Mists)       sern cell mutagenicity         Barmable Liquids       Signal Word       Signal Word       Signal Word         Panger       Plaxard Statements       • Causes serious eye damage.       • Causes serious eye damage.         • Harmful if swallowed.       • Cause drowsiness or dizziness.       • May cause drowsiness or dizziness.	Category 4 Category 1B
Recommended Use:       Protective Coating, this product is for use with Part A onl         Details of the supplier of the safety data sheet       Supplier Address         Supplier Address       Wilko Paint, Inc.         2727 Ohio St.       P.O. Box 4089         Wichita, KS 67204       Toll Free:         Emergency Telephone Number:       Toll Free:       1-800-658-3799         Company Phone Number:       Toll Free:       1-800-424-9300         Emergency Telephone (24 hr):       Chemtrec:       1-800-424-9300         Physical State:       Liquid       Liquid         Classification       Custe toxicity - Inhalation (Dusts/Mists)       Immable Liquids         Signal Word       Immable Liquids       Immable Liquids         May cause serious eye damage.       Immable Liquids.       Immable Liquids.	Category 4 Category 1B
Details of the supplier of the safety data sheet   Supplier Address   Wilko Paint, Inc.   2727 Ohio St.   P.O. Box 4089   Wichita, KS 67204   Emergency Telephone Number:   Company Phone Number:   Signal Word   Danger   Harmful if swallowed.   Harmful if swallowed.   Harmful if swallowed.   Causes skin irritation.   Nay cause respiratory irritation.	Category 4 Category 1B
Supplier Address Wilko Paint, Inc. 2727 Ohio St. P.O. Box 4089 Wichita, KS 67204 Emergency Telephone Number: Company Phone Number: Company Phone Number: Toll Free: 1-800-658-3799 Emergency Telephone (24 hr): Chemtrec: 1-800-424-9300 2. HAZARDS IDENTIFICATION Physical State: Liquid Classification Acute toxicity - Inhalation (Dusts/Mists) Germ cell mutagenicity Harmable Liquids Signal Word Danger Hazard Statements - Flammable liquid and vapor. - Harmful if swallowed. - Causes serious eye damage. - May cause drowsiness or dizziness.	Category 1B
Wite Paint, Inc.         2727 Ohio St.         P.O. Box 4089         Wichita, KS 67204         Emergency Telephone Number:         Company Phone Number:         Company Phone Number:         Toll Free:       1-800-658-3799         Emergency Telephone (24 hr):       Chemtrec:         Demogram       2. HAZARDS IDENTIFICATION         Physical State:       Liquid         Classification	Category 1B
Emergency Telephone (24 hr): Chemtrec: 1-800-424-9300 2. HAZARDS IDENTIFICATION Physical State: Liquid Classification Acute toxicity - Inhalation (Dusts/Mists) Germ cell mutagenicity Planmable Liquids Signal Word Danger Hazard Statements • Flammable liquid and vapor. • Harmful if swallowed. • Causes skin irritation.	Category 1B
P.O. Box 4089 Wichita, KS 67204 Emergency Telephone Number: Company Phone Number: Company Phone Number: Toll Free: 1-800-658-3799 Emergency Telephone (24 hr): Chemtrec: 1-800-424-9300 2. HAZARDS IDENTIFICATION Physical State: Liquid Classification value toxicity - Inhalation (Dusts/Mists) Germ cell mutagenicity Tammable Liquids Signal Word Danger Hazard Statements • Flammable liquid and vapor. • Harmful if swallowed. • Causes skin irritation. • May cause respiratory irritation. • May cause drowsiness or dizziness.	Category 1B
Wichita, KS 67204 Emergency Telephone Number: Company Phone Number: Toll Free: 1-800-658-3799 Emergency Telephone (24 hr): Chemtrec: 1-800-424-9300 C.HAZARDS IDENTIFICATION  Physical State: Liquid Classification ccute toxicity - Inhalation (Dusts/Mists) cerm cell mutagenicity tammable Liquids  Signal Word Danger Hazard Statements • Flammable liquid and vapor. • Harmful if swallowed. • Causes serious eye damage. • May cause respiratory irritation. • May cause respiratory irritation. • May cause drowsiness or dizziness.	Category 1B
Emergency Telephone Number: Company Phone Number: Emergency Telephone (24 hr): Toll Free: 1-800-658-3799 Chemtrec: 1-800-424-9300 2. HAZARDS IDENTIFICATION Physical State: Liquid Classification Acute toxicity - Inhalation (Dusts/Mists) Germ cell mutagenicity Tammable Liquids Signal Word Danger Hazard Statements • Flammable liquid and vapor. • Causes skin irritation.	Category 1B
Company Phone Number:       Toll Free:       1-800-658-3799         Emergency Telephone (24 hr):       Chemtrec:       1-800-424-9300         2. HAZARDS IDENTIFICATION       2. HAZARDS IDENTIFICATION         Physical State:       Liquid         Classification       Classification         Acute toxicity - Inhalation (Dusts/Mists)       Germ cell mutagenicity         Teammable Liquids       Company Phone Number:         Signal Word       Company Phone Number:         Plasmable liquid and vapor.       Causes serious eye damage.         • Flammable liquid and vapor.       May cause respiratory irritation.         • May cause drowsiness or dizziness.       May cause drowsiness or dizziness.	Category 1B
Emergency Telephone (24 hr): Chemtrec: 1-800-424-9300   2. HAZARDS IDENTIFICATION   Physical State: Liquid   Classification   cute toxicity - Inhalation (Dusts/Mists)   Germ cell mutagenicity   iammable Liquids   Signal Word Danger   Hazard Statements   • Flammable liquid and vapor.   • Harmful if swallowed.   • Causes skin irritation.   • Causes drowsiness or dizziness.	Category 1B
2. HAZARDS IDENTIFICATION         Physical State:       Liquid         Classification         Acute toxicity - Inhalation (Dusts/Mists)         Germ cell mutagenicity         Flammable Liquids         Signal Word         Danger         Hazard Statements         • Flammable liquid and vapor.         • Harmful if swallowed.         • Causes skin irritation.	Category 1B
Physical State:       Liquid         Classification       Acute toxicity - Inhalation (Dusts/Mists)         Germ cell mutagenicity       Flammable Liquids         Signal Word       Image:         Danger       Image:         Hazard Statements       • Flammable liquid and vapor.         • Harmful if swallowed.       • Causes skin irritation.         • Causes skin irritation.       • May cause drowsiness or dizziness.	Category 1B
Classification         Acute toxicity - Inhalation (Dusts/Mists)         Germ cell mutagenicity         Planmable Liquids         Signal Word         Danger         Hazard Statements         • Flammable liquid and vapor.         • Harmful if swallowed.         • Causes skin irritation.         • Causes skin irritation.	Category 1B
Danger         Hazard Statements         • Flammable liquid and vapor.         • Harmful if swallowed.         • Causes skin irritation.         • Causes skin irritation.	
<ul> <li>Harmful if swallowed.</li> <li>Causes skin irritation.</li> <li>May cause respiratory irritation.</li> <li>May cause drowsiness or dizziness.</li> </ul>	
<ul> <li>Harmful if swallowed.</li> <li>Causes skin irritation.</li> <li>May cause respiratory irritation.</li> <li>May cause drowsiness or dizziness.</li> </ul>	
Causes skin irritation.     May cause drowsiness or dizziness.	
Other: Harmful if ingested or inhaled. See Sections 8 and 16 for more information.	
Precautionary Statements - Prevention	
Obtain special instructions before use.	1
<ul> <li>Do not handle until all safety precautions have been read and understood.</li> </ul>	
<ul> <li>Use personal protective equipment as required.</li> </ul>	
<ul> <li>Avoid breathing dust/fume/gas/mist/vapors/spray.</li> </ul>	
<ul> <li>Use only outdoors or in a well-ventilated area.</li> </ul>	
ullet Keep away from heat/sparks/open flames/hot surfaces. — No smoking.	
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or s	au an a start
carcinogens. As with any chemicals, asthmatic sensitization can occur from single or repeated exposure	suspected

#### Precautionary Statements - Response

• If exposed or concerned: Get medical advice/attention.

- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

# <u>Precautionary Statements - Storage</u> <u>Precautionary Statements - Disposal</u>

Store locked up and out of reach of children, in a well-ventilated place. Keep cool.

**Dosal** Dispose of contents/container to an approved waste disposal plant.

#### **Other Hazards**

Harmful to aquatic life with long lasting effects.

# 3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Chemical Name	CAS No	Weight - %
Benzyl Alcohol	100-51-6	40-45
N-BUTYL ALCOHOL	71-36-3	15-20
TRIETHYLENETETRAMINE	112-24-3	< 02

\*\* If chemical name is "proprietary" or CAS No. is blank, and weight % is zero or listed as a range, then the specific chemical identity and/or percentage of composition is witheld as a trade secret and any exposure limits is listed in Section 8.

# 4. FIRST AID MEASURES

# First Aid Measures

• General Advice If exposed or concerned: Get medical advice/attention.

- Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Skin Contact Take off contaminated clothing. Wash skin with soap and water. Wash contaminated clothing before reuse.
- Inhalation Remove to fresh air. If not breathing, give artificial respiration.
- **Ingestion** Do not induce vomiting. Call a physician.

**Most important symptoms and effects** May cause skin and eve irritation. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Loss of coordination.

# Indication of any immediate medical attention and special treatment needed Loss of consciousness, fainting. Blurry or loss of vision.

. . . . . . . .

Notes to Physician Treat symptomatically.

#### **5. FIRE FIGHTING MEASURES**

#### FLAMMABILITY CLASSIFICATION

FLAMMABLE LIQUID - NFPA CLASS 2 - Combustible liquid flash point of 100° to 200° F.

#### SUITABLE EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam.

#### SPECIAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

HAZARDOUS COMBUSTION PRODUCTS: Carbon oxides

#### SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus must be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

#### 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

• Use personal protective equipment as required.

- Prevent further leakage or spillage if safe to do so.
- Remove all sources of ignition. Ventilate the area.
- Remove with inert absorbent and place into an appropriate container for disposal.

# 7. HANDLING AND STORAGE

## HANDLING

- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
- Use personal protection recommended in Section 8. Avoid breathing vapors or mists.
- During use and until all vapors are gone: Keep area ventilated Do not smoke Extinguish all flames, pilot lights, and heaters Turn off. stoves, electric tools and appliances, and any other sources of ignition.
- Consult NFPA Code. Use approved Bonding and Grounding procedures. Use spark-proof tools and explosion-proof equipment.

#### STORAGE

- Keep container closed when not in use. Store in a dry, cool and well-ventilated place.
- Transfer only to approved containers with complete and appropriate labeling.
- Do not take internally.
- Keep out of the reach of children.
- Incompatible with strong oxidizing agents.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### PRECAUTIONS TO BE TAKEN IN USING THIS PRODUCT

```
NO person should use this product, or be in the area here it is being used, if they have chronic (long-term) lung or breathing problems or if they ever had a reaction to any one ingredients listed in the table below.
```

- Use only with adequate ventilation.
- Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.
- Wash hands after using.
- This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 3) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 3, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction).

#### **EXPOSURE LIMITS**

ACGIH TLV	OSHA PEL	NIOSH IDLH
TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m3	TWA: 50 ppm TWA: 150 mg/m3

#### Individual protection measures, such as personal protective equipment

Eye/Face Protection	Wear goggles or safety glasses with unperforated side shields.
Skin and Body Protection	Use solvent resistant gloves and apron or suitable protective clothing, additional use of barrier cream is recommended.
Respiratory Protection	Apply in a spray booth with ventilation that is adequate to keep the TWA TLV below the stated limits as stated in the Section 8 table, otherwise use a positive pressure air supplied respirator (TL19C NIOSH/MSHA approved). If unavailable, a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 8 may be used as long as the TWA TLV are below stated limits. Follow respirator manufacturer's directions for use. Wear the respirator for the duration of spraying and until all vapors and mists are gone.
	ALL PERSONELL IN THE AREA WHERE THIS PRODUCT IS BEING USED MUST BE EQUIPPED WITH THE SAME RESPIRATOR PROTECTION RECOMMENDED FOR THE PAINTERS.
	Wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive, when sanding or abrading dried film.

General Hygiene Considerations:

Handle in accordance with good industrial hygiene and safety practice.

#### **OTHER PRECAUTIONS**

If this product is to be mixed with other components before use, read and follow warning labels on all components. Intentional misuse by deliberately concentrating and inhaling the vapors can be harmful or fatal.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Appearance Color	Liquid Paint See description	Odor Odor Threshold	Not determined Not determined	
Property	Values Remarks • Method			
рН	Not determined			
Melting Point/Freezing Point	Not determined			
Boiling Point/Boiling Range	115-278 °C / 239-532 °F			
Flash Point	46 °C / 115 °F			
Evaporation Rate	Slower Than Ether			
Flammability (Solid, Gas)	N/A - Liquid			
Upper Explosive Limit (UEL)	Not determined			
Lower Explosive Limit (LEL)	1.00 %			
Flammability Limit Vapor	Not determined			
Vapor Pressure	Not determined			
Vapor Density	Heavier than air			
Specific Gravity	0.96			
Water Solubility	Not determined			
Solubility in other solvents	Not determined			
Partition Coefficient Auto-	Not determined			
Ignition Temperature	Not determined			
Decomposition	Not determined			
Temperature Kinematic	Not determined			
Viscosity Dynamic	Not determined			
Viscosity	Not determined			
VOC	1.35 #/gal or 162 gr/li		EPA Method 24	
VOC Actual	1.35 #/gal or 162 gr/li		Total VOC per gallon, as supplied	
Wt/Gal	8.02 #/gal			

# **10. STABILITY AND REACTIVITY**

 Reactivity
 Not reactive under normal conditions.

 Chemical Stability
 Stable under recommended storage conditions.

 Possibility of Hazardous Reactions
 None under normal processing.

 Conditions to Avoid
 Avoid all possible sources of ignition.

 Incompatible Materials
 Strong oxidizing agents.

 Hazardous Decomposition Products
 Carbon oxides.

# **11. TOXICOLOGICAL INFORMATION**

There is no specific data available for this product.

#### **12. ECOLOGICAL INFORMATION**

There is no specific data available for this product.

CAUTION:Can be toxic to living organisms. Keep out of soil and water stream.ECOTOXICITY EFFECTS:Harmful to aquatic life with long lasting effects.MOBILITY:Not availableBIOACCUMULATIVE POTENTIAL:Not availablePERSISTANCE / DEGRADABILITY:Not available

#### **13. DISPOSAL CONSIDERATIONS**

#### WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Disposal should be in accordance with applicable regional, national and local laws and regulations. Only EPA approved facility must handle incineration if this method of disposal is chosen.

**Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations (Refer to above).

14. TRANSPORT INFORMATION				
NOTE	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.			
UN/ID No	UN 1263			
Proper Shipping Name	Paint			
Hazard Class	3			
Packing Group	III			
IATA				
UN/ID No	UN 1263			
Proper Shipping Name	Paint			
Hazard Class	3			
Packing Group	III			
<u>IMDG</u>				
UN/ID No	UN 1263			
Proper Shipping Name	Paint			
Hazard Class	3			
Packing Group	III			

# **15. REGULATORY INFORMATION**

There is no specific data available for this product.

16. OTHER INFORMATION					
NFPA		Health Hazards 2*	<b>Flammability</b> 3	<b>Instability</b> 1	Special Hazards Not Determined
HMIS		Health Hazards *2	<b>Flammability</b> 2	Physical Hazards 1	Personal Protection J,X**
Chronic Hazard Personal Protect					
Issue Date: Revision Date: Version: Revision Note:	17-Jun-1993 13-May-2016 A SDS format				

#### <u>Disclaimer</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### End of Safety Data Sheet